

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf
MSDS Number : 000000011078
Product Use Description : Refrigerant

Company : Honeywell International, Inc.
101 Columbia Road
Morristown, NJ 07962-1057

For more information call : 800-522-8001
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-651-523-0309**
: **Transportation: 1-800-424-9300 or +1-703-527-3887**
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : clear

Odor : slight

Hazard Summary : Warning! Container under pressure. Flammable gas. Gas reduces oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause drowsiness and dizziness. May cause skin irritation. May cause eye irritation. May cause respiratory tract irritation. Do not breathe vapour. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250 C), decomposition products may include hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

Potential Health Effects

Skin : Avoid skin contact with leaking liquid (danger of frostbite).
May cause frostbite.

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

- May cause skin irritation.
- Eyes : May cause frostbite.
May irritate eyes.
- Ingestion : Unlikely route of exposure.
Effects due to ingestion may include:
Gastrointestinal discomfort
- Inhalation : May be harmful if inhaled.
May cause respiratory tract irritation.
Gas reduces oxygen available for breathing.
Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating.
Inhalation may cause central nervous system effects.
Vapours may cause drowsiness and dizziness.
- Chronic Exposure : None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Substance

Chemical Name	CAS-No.	Concentration
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	100.00%

SECTION 4. FIRST AID MEASURES

- General advice : First aider needs to protect himself. Take off all contaminated clothing immediately.
- Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.
- Skin contact : After contact with skin, wash immediately with plenty of water. Rapid evaporation of the liquid may cause frostbite. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

- similar covering. Call a physician. Wash contaminated clothing before re-use.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. Call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. If conscious, drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician immediately.

Notes to physician

- Treatment : Treat frost-bitten areas as needed. Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Flash point : not applicable
- Ignition temperature : 405 °C (761 °F)
- Lower explosion limit : 6.2 %(V)
- Upper explosion limit : 12.3 %(V)
- Suitable extinguishing media : In case of fire, allow gas to burn if flow cannot be shut off immediately.
Apply water from a safe distance to cool container and protect surrounding area.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during fire fighting : Flammable gas.
Contents under pressure.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
Fire or intense heat may cause violent rupture of packages.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
In case of fire hazardous decomposition products may be produced such as:

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

Hydrogen fluoride
 Carbonyl halides
 Carbon monoxide
 Carbon dioxide (CO₂)

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus and protective suit. No unprotected exposed skin areas.

Additional advice : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Wear personal protective equipment. Unprotected persons must be kept away. Wear self-contained breathing apparatus and protective suit. Eliminate all ignition sources if safe to do so. Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Avoid accumulation of vapours in low areas. Unprotected personnel should not return until air has been tested and determined safe. Ensure that the oxygen content is $\geq 19.5\%$.

Environmental precautions : Prevent further leakage or spillage if safe to do so. The product evaporates readily. Discharge into the environment must be avoided.

Methods for cleaning up : Use explosion-proof equipment. No sparking tools should be used. Ventilate the area. Allow to evaporate.

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Handle with care. Wear personal protective equipment.

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

Do not breathe vapour.
 Avoid contact with skin, eyes and clothing.
 Use only in well-ventilated areas.
 Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
 Follow all standard safety precautions for handling and use of compressed gas cylinders.
 Use authorized cylinders only.
 Protect cylinders from physical damage.
 Do not puncture or drop cylinders, expose them to open flame or excessive heat.
 Do not remove screw cap until immediately ready for use.
 Always replace cap after use.

Advice on protection against fire and explosion : Container hazardous when empty.
 Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
 Keep product and empty container away from heat and sources of ignition.
 Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
 Take measures to prevent the build up of electrostatic charge. Electrical equipment should be protected to the appropriate standard.
 Use explosion-proof equipment.
 No sparking tools should be used.
 No smoking.

Storage

Requirements for storage areas and containers : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
 Keep containers tightly closed in a dry, cool and well-ventilated place.
 Keep away from heat and sources of ignition.
 Storage rooms must be properly ventilated.
 Ensure adequate ventilation, especially in confined areas.
 Protect cylinders from physical damage.
 Store away from incompatible substances.
 Store in original container.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

the workstation location.
Do not breathe vapour.
Avoid contact with skin, eyes and clothing.

- Engineering measures : Use with local exhaust ventilation.
- Eye protection : Safety goggles
- Hand protection : Protective gloves
Gloves must be inspected prior to use.
Replace when worn.
- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
Wear suitable protective equipment.
- Respiratory protection : No personal respiratory protective equipment normally required.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Use NIOSH approved respiratory protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
When using, do not eat, drink or smoke.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.
Do not breathe vapour.
Avoid contact with skin, eyes and clothing.

Exposure Guidelines

2,3,3,3-Tetrafluoroprop-1-ene	754-12-1	WEEL	TWA	500 ppm
		HONEYWELL	TWA	500 ppm
		We are not aware of any national exposure limit.		
		HONEYWELL	STEL	1,500 ppm
		We are not aware of any national exposure limit.		

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquefied gas
- Color : clear
- Odor : slight

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

Molecular Weight	: 114 g/mol
pH	: no data available
Boiling point/boiling range	: -29.4 °C (-20.9 °F)
Vapor pressure	: 6,067 hPa at 21.1 °C (70.0 °F)
Vapor pressure	: 14,203 hPa at 54.4 °C (129.9 °F)
Relative vapour density	: 4 (Air = 1.0)
Density	: 1.1 g/cm ³ at 25 °C (77 °F)
Water solubility	: 198.2 mg/l at 24 °C (75 °F) 92/69/EEC, A.6
Partition coefficient: n-octanol/water	: log Pow: 2.15 92/69/EEC, A.8

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid	: Keep away from heat and sources of ignition. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Decomposes under high temperature. Some risk may be expected of corrosive and toxic decomposition products.
Materials to avoid	: Strong oxidizing agents Finely divided aluminium Magnesium Zinc
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: Hydrogen fluoride Carbonyl halides Carbon monoxide

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

Carbon dioxide (CO₂)

Hazardous reactions : Hazardous polymerisation does not occur.
Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: > 400000 ppm
Exposure time: 4 h
Species: rat

Sensitisation : Cardiac sensitization
Species: dogs
Result: No effects observed for exposures up to 12% (120,189 ppm).

Repeated dose toxicity : Species: rat
Application Route: Inhalation
Exposure time: 2 Weeks
Note: NOEL - 50,000 ppm

: Species: rat
Application Route: Inhalation
Exposure time: 4 Weeks
Note: NOAEL (No observed adverse effect level) - 50,000 ppm

: Species: rat
Application Route: Inhalation
Exposure time: 13 Weeks
Note: NOAEL (No observed adverse effect level) - 50,000 ppm

Genotoxicity in vitro : Test Method: Ames test
Result: 20% and higher, positive in TA 100 and e. coli WP2 uvrA, negative in TA98, TA100, and TA1535.

: Test Method: Chromosome aberration test in vitro
Cell type: Human lymphocytes
Result: negative
Note: Dose 760,000 ppm

: Test Method: Chromosome aberration test in vitro
Cell type: Chinese Hamster Lung Cells
Result: negative

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

Genotoxicity in vivo	:	Species: mouse Cell type: Micronucleus Dose: up to 200,000 ppm (4 hour) Result: negative
Genotoxicity in vivo	:	Test Method: Unscheduled DNA synthesis Dose: up to 50,000 ppm (4 week) Result: negative
Genotoxicity in vivo	:	Species: rat Cell type: Micronucleus Dose: up to 50,000 ppm (4 week) Result: negative
Teratogenicity	:	Species: rat Dose: NOAEL (No observed adverse effect level) - 50,000 ppm Species: rabbit Dose: NOAEL (No observed adverse effect level) - 4,000 ppm

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity effects**

Toxicity to fish	:	LC50: > 197 mg/l Exposure time: 96 h Species: Cyprinus carpio (Carp) Method: OECD Test Guideline 203 Note: No demonstrable toxic effect in saturated solution.
Toxicity to daphnia and other aquatic invertebrates.	:	EC50: > 83 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202
Toxicity to algae	:	EC50: > 100 mg/l Species: Scenedesmus capricornutum (fresh water algae)

Elimination information (persistence and degradability)

Biodegradability	:	Result: Not readily biodegradable.
------------------	---	------------------------------------

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

Further information on ecology**SECTION 13. DISPOSAL CONSIDERATIONS**

Waste Information: Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT	UN/ID No.	: UN 3161
	Proper shipping name	: LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoroprop-1-ene)
	Class	: 2.1
	Packing group	
	Hazard Labels	: 2.1

IATA	UN/ID No.	: UN 3161
	Description of the goods	: LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoroprop-1-ene)
	Class	: 2.1
	Hazard Labels	: 2.1
	Packing instruction (cargo aircraft)	: 200

IMDG	UN/ID No.	: UN 3161
	Description of the goods	: LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-TETRAFLUOROPROP-1-ENE)
	Class	: 2.1
	Hazard Labels	: 2.1
	EmS Number	: F-D
Marine pollutant	: no	

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances Control Act : On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act : Not in compliance with the inventory

Canada. Canadian : 2,3,3,3-Tetrafluoroprop-1-ene 754-12-1
: This product contains the following components that are not on

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 144)	the Canadian DSL nor NDSL lists.
Japan. Kashin-Hou Law List	: 2,3,3,3-Tetrafluoroprop-1-ene 754-12-1 : On the inventory, or in compliance with the inventory
Korea. Existing Chemicals Inventory (KECI)	: On the inventory, or in compliance with the inventory
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	: Not in compliance with the inventory
China. Inventory of Existing Chemical Substances	: 2,3,3,3-Tetrafluoroprop-1-ene 754-12-1 : Not in compliance with the inventory
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	: 2,3,3,3-Tetrafluoroprop-1-ene 754-12-1 : Not in compliance with the inventory
TSCA 12B	: 2,3,3,3-Tetrafluoroprop-1-ene 754-12-1 : US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)
	2,3,3,3-Tetrafluoroprop-1-ene 754-12-1

National regulatory information

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Sudden Release of Pressure Hazard

2,3,3,3-Tetrafluoroprop-1-ene, HFO-1234yf

Version 1

Revision Date 02/16/2011

Print Date 02/16/2011

California Prop. 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

New Jersey RTK : 2,3,3,3-Tetrafluoroprop-1-ene 754-12-1

Pennsylvania RTK : 2,3,3,3-Tetrafluoroprop-1-ene 754-12-1

WHMIS Classification : B1
A
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 4	4
Physical Hazard	: 0	
Instability	:	0